



Freecom TapeWare LTO2-HH EZ Kits – High performance backup with up to 400 GB*



Freecom LTO2-HH EZ-Kits

- Based on leading Quantum LTO-technology
- Fastest LTO2-HH drive in the market today
- Saves up to 400* GB of data on a single data cartridge in less than 2 hours and 15 minutes*
- Up to 187.2* GB/h data transfer rate
- Twice capacity of LTO1 and more than two times faster than LTO1-HH
- Lowest price per GB in comparison to other tape technologies*
- Internal 5.25"-Solution (half height)
- Dynamic speed matching (adapts the speed of the Host)
- MTBF at 250.000 hours at permanent use (100% duty cycle)
- Offers LTO2 Capacity to an affordable SMB pricing
- Supporting most of the operating systems and platforms like e. g. Windows, NetWare, Linux, MAC OS, Unix
- 3 years express exchange warranty
- WEEE/ROHS ready

* Capacities and transfer rates quoted as typical use a 2:1 compression ratio

Package includes

- LTO-Ultrium-2 device, 5.25" half height, internal
- SCSI cable
- User manual on CD
- 3 years express exchange warranty after user registration

Freecom TapeWare LTO2-HH EZ Kit

Capacity	200 - 400* GB with LTO Ultrium 2 Media
Recording Format	Ultrium Generation 2
Performance	26 – 52* MB/sec
Data access time	58 sec. from beginning of tape (average)
Interface	Ultra 160 SCSI
Buffer size	64 MB
Hardware data compression	ALDZ-2
Form Factor	5.25", half height
Reliability/MTBF	250.000 hours at permanent use (100% duty cycle)
Hard Error Rate	1×10^{-17}
Loading Mechanism	Electronical loading of the media, precision ejection
Compatibility	LTO Ultrium 1 ^{1,2} , LTO Ultrium 2 ^{1,2}
Power Requirements	Stand by 17 W Operation (avarage) 30 W Operation (maximum) 34 W
Enviromental conditions Temperature	-40°C (-40° F) to 66° C (151° F) (stocking) 10° C (50° F) bis 40° C (104° F) (operation)
Humidity range	Stocking: 10% bis 95% (relative humidity, non condensing) Operation: 20% bis 80% (relative humidity, non condensing)
Dimensions (h x w x d)	43.4 x 148.1 x 227.0 mm (1.7 x 5.8 x 8.9 inches)
Weight	Internal: 1.50 kg (3.3 lbs)
Media Capacity	100 - 200* GB (LTO-1), 200 - 400* GB (LTO-2)
Certifications	CSA, TÜV,CE, FCC, NOM, VCCI, C-Tick, RRL, BSMI, GOSH, CB, WEEE/ ROHS ready

* Capacities and transfer rates quoted as typical use a 2:1 compression ratio

¹ read, ² write

FC TapeWare	LTO2-Hhi EZ-Kit
Art. No. EU/UK	25044
EAN Code EU/UK	4021801250445
Capacity	200-400* GB